

# VIKING

# TECHNICAL Practice

**TELECOM SOLUTIONS FOR THE 21ST CENTURY**

**K-1200**  
**K-1200-EWP**  
*Multi-Button Handsfree*  
*Entry Phone*  
July 10, 2007

## 12 Button Apartment Entry Phone with Built in Door Strike Relay



Model K-1200 (shown in optional VE-5x10-SS, not included)

The **K-1200** Entry Phone is a two way, hands free telephone with 12 buttons for calling individual residences in an apartment building. The rugged stainless steel faceplate has a printed directory housed in a water proof plastic lens. Each button is beside the tenants name in the directory so there are no confusing codes to deal with. Calling a particular tenant is as easy as pressing a single button. The **K-1200** has a built in speed dialer that can handle up to 12 primary phone numbers, each with 32 digits. If there is no answer at the first number, a second number can be called automatically. Once the tenant answers their phone, a single touch tone command can activate the door strike relay. For no-CO applications, the **K-1200** is compatible with the **C-3000** No CO Controller.

For outdoor applications, the **K-1200** is available with Enhanced Weather Protection. EWP products feature rubber gaskets and boots, closed cell foam gasketing, hand soldered silicon sealed connections, anti-corrosive gel filled butt connectors, as well as urethane encapsulated circuit boards with internally sealed trim POTS and DIP switches.

## Features

- Operates on 12 to 24 volts AC/DC
- 12 speed dial buttons (each up to 32 digits)
- 12 second number positions (each with 32 digits)
- One button operation (no call button)
- Hang-up on CPC, busy, silence, time-out or dial tone return
- Touch Tone restriction from microphone
- Integral relay for camera control or door strike
- Works with **C-1000B** for increased security
- Works with **C-3000** for "No CO" operation
- Optional Enhanced Weather Protection (EWP)
- **VE-LIGHT** compatible

## Applications

- Small apartment buildings
- Professional buildings
- Gated communities

Phone... 715.386.8861

<http://www.vikingelectronics.com>

[info@vikingelectronics.com](mailto:info@vikingelectronics.com)

## Specifications

**Power:** 12 to 24 Volts AC or DC, 12VDC adapter provided  
**Dimensions:** 127mm x 254mm x 63.5mm (5" x 10" x 2.5")  
**Shipping weight:** kg ( lbs.)  
**Operating Temp:** -35°C to 66°C (-30°F to 150°F)  
**Relay Contact Rating:** 5A @ 30VDC/250VAC Maximum  
**Connections:** (8) gel-filled butt connectors (3M Scotchlok UR2)